

Fuse plug - PV-C-M/F-PRO/F-1000/15-EU - 1622156

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fuse connector for protecting modules and devices in photovoltaic systems, black, SUNCLIX pin connector pattern, 1000 V/15 A, IP68 (24 h/2 m)

SUNCLIX fuse connector, in the version for 1000 V system voltage

Product Description


SUNCLIX fuse connector, for 1000 V system voltage, fuse-link nominal current of 15 A, EU version

Why buy this product

- One-piece design
- Robust, easy-to-install fuse element for outdoor use
- High-quality fuse-link
- Degree of protection: IP68 (24 h/2 m)
-
- 1000 V (EN)



Key Commercial Data

| | |
|------------------------|---|
| Packing unit | 8 STK |
| Minimum order quantity | 8 STK |
| GTIN |  4 055626 130729 |
| GTIN | 4055626130729 |

Technical data

Ambient conditions

| | |
|--|--------------------------|
| Degree of protection (when plugged in) | IP66 / IP68 (2 m / 24 h) |
| Ambient temperature (operation) | -40 °C ... 50 °C |

General

| | |
|------------------------------|--|
| Rated voltage | 1000 V |
| Fuse-link nominal current | 15 A DC (Nominal current of the fuse-link) |
| Fuse adapter nominal current | 15 A DC |

Fuse plug - PV-C-M/F-PRO/F-1000/15-EU - 1622156

Technical data

Material

| | |
|--|----|
| Flammability rating according to UL 94 | V0 |
|--|----|

Standards and Regulations


| | |
|--|----|
| Flammability rating according to UL 94 | V0 |
|--|----|

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Drawings

Dimensional drawing



Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>