

Revision level		Revision Record	Changed	Date	Approved	Date
part	drawing					
—	01	See ECN 011616	A.A.C.	08/27/10	K.A.C.	08/31/10

HOUSING:
POLYCARBONATE

Material

Dimension tolerances
unless otherwise specified

.XXX = ± .0130
.XXX = ± .300
.XX = ± .30
.X = ± .2
∠ = ± 0.5 °

Dimension Units mm


Stripping Length:

11mm(.45 in)
Wire Range:
0.5–2.5 mm²
Solid/Stranded(VDE)
(12–22 AWG
Solid/Stranded) MAX 7
Cores
Working Temp:
–30°C(–22°F)to
110°C(230°F) (VDE)
–22°F(–30°C) to
221°F(105°C) (cULus)


Voltage:
600V(cULus)
Current:
24A

Certifications:
UL E316080, KEMA–KEUR
VDE,FIMKO,ENEC,CEBEC,
NEMKO, DEMKO

PERFORMANCE
SPECIFICATION



ACAD MECH
2009



Drawn	A.A.C.	08/27/10
Approved	K.A..C.	08/31/10

Scale: NTS
Computer File Number
WC\CST\XWC-HPR015CSU_01

Title
HECP-5 Phase: Production

ALL PROPRIETARY RIGHTS IN THE
SUBJECT MATTER SHOWN ON THIS
DRAWING ARE EXCLUSIVE
PROPERTY OF HELLERMANNTYTON

HellermannTyton

7930 N. Faulkner Rd.
Milwaukee, WI 53224
Ph: (414) 355-1130
Fx: (414) 362-8342

**HECP-5
HELACON PLUS
PUSH-IN WIRE CONNECTOR**

Drawing-No

XWC-HPR015CSU

Format
AH
Sheet 1 of 1