



NOTES:

1. INSERTION LOSS: 0.75 dB MAX.
2. OPERATION TEMP: -20°C TO +70°C.
3. PRODUCT COMES WITH DUST CAPS. (NOT SHOWN)
4. MATERIALS:
 SLEEVE:
 SINGLE-MODE - CERAMIC (ZIRCONIA)
 MULTI-MODE - PHOSPHORUS BRONZE
 HOUSING - DELRIN, BLACK
 ADAPTER - THERMOPLASTIC
 ADAPTER MOUNTING CLIPS - STAINLESS STEEL
5. FOR MOUNTING SCREWS TO BE SHIPPED WITH ASSEMBLY AND INDIVIDUAL PACKAGING, ADD SUFFIX -PKG TO PART NUMBER.
6. WHEN MOUNTING ASSEMBLY, USE A SCREW TORQUE OF 10 INCH-POUNDS MAXIMUM.
7. THIS PRODUCT IS RoHS COMPLIANT.

**RECOMMENDED
PANEL CUT-OUT**

| PART NUMBER | SC2 ADAPTER | ADAPTER COLOR |
|-------------|-------------|---------------|
| EHSC2 | SINGLE-MODE | BLUE |
| EHSC2M | MULTI-MODE | BEIGE |

CUSTOMER DRAWING

| | | | | | | | | | |
|-----------|------------|---------|----|------|--|-------|-----------|--------------|---------------------|
| | | | | | THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY. | | | | |
| | | | | | SIZE | WIDTH | MULT | LBS/M | TEMPER |
| | | | | | FINISH | | | MATERIAL | |
| | | | | | SPEC No. | | | SPEC No. | |
| | | | | | FIRST USED ON | | SCALE 1:1 | | |
| A | 26348 | 2/27/29 | RS | TJK | DATE DRAWN | BY | CHKD | APVD | Switchcraft® |
| REV | ECO NUMBER | DATE | BY | APVD | 5/12/08 | JGK | RS | TJK | |
| REVISIONS | | | | | DO NOT SCALE DRAWING | | | | |
| | | | | | NAME | | | PART No. | |
| | | | | | E SERIES SC/SC FIBER OPTIC ADAPTER, RoHS | | | EHSC2 SERIES | |
| | | | | | REV A | | | | |

