



SECTION Z-Z

MATED DRAWING

11.8	15.1	19.7	22.6	560020-0800	8
11.8	13.1	17.7	20.6	560020-0700	7
11.8	12	15.7	18.6	560020-0600	6
9.8	10	13.7	16.6	560020-0500	5
7.8	8	11.7	14.6	560020-0400	4
5.8	6	9.7	12.6	560020-0300	3
6.3		8.0	10.9	560020-0200	2
D	C	B	A	EMBOSSED PACKAGE ORDER NO.	CKTS

注記 NOTES

- 材質
ウエハー：耐熱性ナイロン
ピン、フィッティングネール：銅合金、ニッケル下地、錫メッキ
MATERIAL
WAFER: POLYAMIDE
PIN, FINNING NAIL: COPPER ALLOY, TIN OVER NICKEL PLATE.
- 色：ナチュラル
COLOR: NATURAL
- 嵌合相手：
ハウジング:502351-**00
端子:50212-8*00,50372-8*00,560085-0101
MATES WITH
HOUSING:502351-**00
TERMINAL: 50212-8*00,50372-8*00,560085-0101
- エンボス梱包品の詳細はSD-560020-002参照
DETAILED TAPING PACKAGE, SEE SD-560020-002
- ELV及びRoHS適合
ELV AND RoHS COMPLIANT

REVISED EC NO.: JTR2014-0081 DRAWN: YAMAKI 2013/07/18 CHKD: HKOMATSU 2013/07/18 APPR: MAYAMOTO 2014/04/11	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY	SCALE 5:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION
	10 UNDER	±0.2	DRAWN BY SHSHIBATA	DATE 2009/02/18	TITLE 2.0MM PITCH W/B CONN. WAFER ASSY ST. SMT	
	10 OVER 30 UNDER	±0.25	CHECKED BY HKOMATSU	DATE 2009/02/18		
	30 OVER	±0.3	APPROVED BY AKANESHIGE	DATE 2009/02/18		
ANGULAR	±1°	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE CHART	DOCUMENT NO. SD-560020-001	SHEET NO. 1 OF 1
SIZE A3	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					