

## Specification Sheet

Part Number: LKCRF19C2



Low Profile Rivet Mount .938"X.47"-PA66, NA, Mnt Hole .25", Max Pan .134", T18-T50 Ties, 100/pk

<b>Article Number</b>	151-27000
<b>Type</b>	LKCRF1
<b>Color</b>	Natural (NA)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• The low-profile rivet mount is designed to secure wiring bundles and fastens with the drive rivet through a predrilled hole.</li><li>• This mount is ideal for use in applications where space is limited.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	HellermannTyton's Mounts with Rivets are ideal for use in applications where space is limited and is designed to secure wiring bundles. Fastens with the drive rivet through a predrilled hole.
<b>Short Description</b>	Low Profile Rivet Mount .938"X.47"-PA66, NA, Mnt Hole .25", Max Pan .134", T18-T50 Ties, 100/pk

**Global Part Name**

LKCRF1-PA66-NA

**Length L (Imperial)**

0.938

**Length L (Metric)**

24.0

**Fixation Method**

with Rivet (Mounts)

**Width W (Imperial)**

0.47

**Width W (Metric)**

12.0

**Cable Ties**

T18 - T50

**Height H (Imperial)**

0.157

**Height H (Metric)**

3.99

**Panel Thickness Max(Imperial)**

0.134

**Panel Thickness Max (Metric)**

3.40

**Mounting Hole Diameter D (Imperial)**

0.25

**Mounting Hole Diameter D (Metric)**

6.4 mm

**Mounting Hole Diameter D Max (Imperial)**

0.255

**Mounting Hole Diameter D Max (Metric)**

6.4

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature (Metric)</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	100
<b>Package Quantity (Metric)</b>	100
<b>Customs Number</b>	3926909987