

Patch panels - FL PF 2TX CAT 6 - 2891068

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Patch field with two RJ45 CAT6 network connections

Why buy this product

- Flexibility through the replacement of patch elements with fiber optic patch elements - Future proof through standardized installation according to CAT5 and CAT6
- Future proof through standardized installation according to CAT5 and CAT6
- Security through extension with FL PLUG GUARD



Key Commercial Data

| | |
|--------------|---|
| Packing unit | 1 STK |
| GTIN |  4 046356 084383 |
| GTIN | 4046356084383 |

Technical data

Dimensions

| | |
|--------|--------|
| Width | 38 mm |
| Height | 112 mm |
| Depth | 88 mm |

Ambient conditions

| | |
|--|---------------------------------|
| Degree of protection | IP20 |
| Ambient temperature (operation) | 0 °C ... 55 °C (non-condensing) |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |
| Permissible humidity (operation) | 10 % ... 95 % (non-condensing) |
| Permissible humidity (storage/transport) | 10 % ... 95 % (non-condensing) |

Interfaces

| | |
|--------------|-----------------|
| Interface 1 | Ethernet (RJ45) |
| No. of ports | 2 |

Patch panels - FL PF 2TX CAT 6 - 2891068

Technical data

Interfaces

| | |
|-------------------|-----------|
| Connection method | RJ45 CAT6 |
|-------------------|-----------|

Conformity with EMC directives

| | |
|---------------------------------|---|
| Developed in acc. with standard | ISO/IEC 11801, EN 50173, TIA/EIA 568B and IEC 60603-7 |
|---------------------------------|---|

General

| | |
|------------------|---------|
| Net weight | 120.2 g |
| Housing material | Metal |

Standards and Regulations

| | |
|---------------------------------|---|
| Developed in acc. with standard | ISO/IEC 11801, EN 50173, TIA/EIA 568B and IEC 60603-7 |
|---------------------------------|---|

Connection data

| | |
|------------------------------|--|
| Conductor cross section | 0.2 mm ² ... 0.32 mm ² |
| Connection cross section AWG | 24 ... 22 |
| Rated voltage (III/3) | 50 V |
| Rated surge voltage | ≥ 1 kV |
| Rated current | 1 A |

Phoenix Contact 2017 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>